



MATERIAL SAFETY DATA SHEET

SIKADUR 35, HI-MOD LV LPL - PART B

HMIS

HEALTH 3

FLAMMABILITY 0

REACTIVITY 0

PERSONAL PROTECTION C

1. Product And Company Identification

Supplier

SIKA CORPORATION
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: Kristin Kelley
Telephone Number: (201) 933-8800
FAX Number: (201) 933-9379
Web Site: www.sikausa.com

Manufacturer

SIKA CORPORATION
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: Kristin Kelley
Telephone Number: (201) 933-8800
FAX Number: (201) 933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 11/09/2001

Product Name: SIKADUR 35, HI-MOD LV LPL - PART B

CAS Number: Not Established

Chemical Family: AMINE COMPOUND

Chemical Formula: RMF-1552

MSDS Number: 818

Product Code: NO. 350-L

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AROMATIC HYDROCARBON BLEND	68477-31-6	
BENZYL ALCOHOL	100-51-6	
BLEND OF CYCLIC AND ALIPHATIC AMINES AND THEIR ADDUCTS	Not Establis	

3. Hazards Identification

Eye Hazards

MAY CAUSE SEVERE BURNS AT SITE OF CONTACT. MAY CAUSE VISUAL DISTURBANCES, CORNEA DAMAGE, DAMAGE TO THE OPTIC NERVE OR BLINDNESS.

Skin Hazards

CORROSIVE, CONTACT MAY CAUSE SEVERE IRRITATION AND PAIN AND MAY CAUSE BURNS, NECROSIS AND PERMANENT INJURY. PROLONGED AND/OR REPEATED CONTACT WITH SKIN MAY CAUSE AN ALLERGIC REACTION/SENSITIZATION.

MATERIAL SAFETY DATA SHEET

SIKADUR 35, HI-MOD LV LPL - PART B

3. Hazards Identification - Continued

Ingestion Hazards

MAY CAUSE EFFECTS TO THE GI TRACT, SUCH AS IRRITATION, NAUSEA, GI DISORDERS, ULCERATION, DIARRHEA OR CONSTIPATION. HARMFUL IF ASPIRATED INTO LUNGS.

Inhalation Hazards

MAY CAUSE RESPIRATORY TRACT IRRITATION. MAY CAUSE RESPIRATORY SENSITIZATION.

4. First Aid Measures

Eye

RINSE EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN.

Skin

WASH SKIN THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. IF SYMPTOMS PERSIST, CONSULT PHYSICIAN.

Ingestion

DILUTE WITH WATER. DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.

Inhalation

REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, INSTITUTE ARTIFICIAL RESPIRATION. CONSULT WITH PHYSICIAN.

5. Fire Fighting Measures

Flash Point: N/AV °F

Autoignition Point: N/AV °F

Flammability Class: N/AV

Lower Explosive Limit: N/AV

Upper Explosive Limit: N/AV

Fire And Explosion Hazards

NONE KNOWN

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

WEAR SUITABLE PROTECTIVE EQUIPMENT. CONTAIN SPILL AND COLLECT WITH ABSORBENT MATERIAL AND TRANSFER INTO SUITABLE CONTAINERS. AVOID CONTACT.

7. Handling And Storage

Handling And Storage Precautions

STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation.

MATERIAL SAFETY DATA SHEET

SIKADUR 35, HI-MOD LV LPL - PART B

8. Exposure Controls/Personal Protection - Continued

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

AVOID SKIN CONTACT. WEAR LONG SLEEVE SHIRT, LONG PANTS & CHEMICAL RESISTANT GLOVES.

Respiratory Protection

In areas where the P.E.L.s are exceeded, use a properly fitted NIOSH-approved respirator.

Other/General Protection

WASH THOROUGHLY AFTER HANDLING.

Ingredient(s) - Exposure Limits

AROMATIC HYDROCARBON BLEND

ACGIH: NOT ESTABLISHED

OSHA: NOT ESTABLISHED

NTP N/AP

IARC N/AP

BLEND OF CYCLIC AND ALIPHATIC AMINES AND THEIR ADDUCTS

ACGIH: NOT ESTABLISHED

OSHA: NOT ESTABLISHED

NTP N/AP

IARC N/AP

9. Physical And Chemical Properties

Appearance

CLEAR, YELLOW TO AMBER LIQUID

Odor

AMINE

Chemical Type: Mixture

Physical State: Liquid

Melting Point: N/AV °F

Boiling Point: N/AV °F

Specific Gravity: 0.98

Percent Volatiles: N/AV

Packing Density: 8.21 #/GAL

Vapor Pressure: N/AV

Vapor Density: N/AV

Solubility: N/AV

Evaporation Rate: N/AV

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR

Conditions To Avoid (Stability)

NONE KNOWN

Incompatible Materials

STRONG OXIDIZING AGENTS, ACIDS AND EPOXY RESINS UNDER UNCONTROLLED CONDITIONS.

MATERIAL SAFETY DATA SHEET

SIKADUR 35, HI-MOD LV LPL - PART B

10. Stability And Reactivity - Continued

Hazardous Decomposition Products

CO, CO2, OXIDES OF NITROGEN

11. Toxicological Information

Miscellaneous Toxicological Information

Conditions Aggravated By Exposure

EYE DISEASE, SKIN DISORDERS OR ALLERGIES, CHRONIC RESPIRATORY DISORDERS.

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Proper Shipping Name

CORROSIVE LIQUID N.O.S. (AMINES)

Hazard Class

8, PG II

DOT Identification Number

UN1760

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard
Chronic Health Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

Ingredient(s) - State Regulations

BENZYL ALCOHOL
New Jersey - Workplace Hazard
Pennsylvania - Workplace Hazard
Massachusetts - Hazardous Substance

16. Other Information

HMIS Rating

Health: 3
Fire: 0
Reactivity: 0
PPE: C

MATERIAL SAFETY DATA SHEET

SIKADUR 35, HI-MOD LV LPL - PART B

Disclaimer

The data in this Material Safety Data Sheet relates only to the specific material herein and does not relate to use in combination with any other material or in any process. The information set forth herein is based on technical data that Sika believes to be reliable as of the date hereof. Since conditions of use are outside our control, we make no warranties, express or implied and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000