



# MATERIAL SAFETY DATA SHEET

## Sikagard 62 - Part A (ALL COLORS)

### HMIS

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

### 1. Product And Company Identification

<u>Supplier</u> <b>Sika Corporation</b> 201 Polito Ave Lyndhurst, NJ 07071  <b>Company Contact:</b> EHS Department <b>Telephone Number:</b> 201-933-8800 <b>FAX Number:</b> 201-933-9379 <b>Web Site:</b> www.sikausa.com	<u>Manufacturer</u> <b>Sika Corporation</b> 201 Polito Ave Lyndhurst, NJ 07071  <b>Company Contact:</b> EHS Department <b>Telephone Number:</b> 201-933-8800 <b>FAX Number:</b> 201-933-9379 <b>Web Site:</b> www.sikausa.com
<u>Supplier Emergency Contacts &amp; Phone Number</u> <b>CHEMTREC: 800-424-9300</b> <b>INTERNATIONAL: 703-527-3887</b>	<u>Manufacturer Emergency Contacts &amp; Phone Number</u> <b>CHEMTREC: 800-424-9300</b> <b>INTERNATIONAL: 703-527-3887</b>

**Issue Date:** 01/24/2006  
**Product Name:** Sikagard 62 - Part A (ALL COLORS)  
**CAS Number:** Not Established  
**Chemical Family:** Epoxy Compound  
**MSDS Number:** 3838  
**Product Code:** 0601130

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AROMATIC HYDROCARBON BLEND	68477-31-6	
EPOXY RESIN	25085-99-8	

### 3. Hazards Identification

**Eye Hazards**  
 EYE IRRITANT.

**Skin Hazards**  
 MAY CAUSE SKIN IRRITATION. PROLONGED AND/OR REPEATED CONTACT WITH SKIN MAY CAUSE AN ALLERGIC REACTION/SENSITIZATION.

**Ingestion Hazards**  
 ACUTELY TOXIC. HARMFUL IF ASPIRATED INTO LUNGS.

# MATERIAL SAFETY DATA SHEET

## Sikagard 62 - Part A (ALL COLORS)

### 3. Hazards Identification - Continued

#### Inhalation Hazards

MAY CAUSE RESPIRATORY TRACT IRRITATION.

### 4. First Aid Measures

#### Eye

RINSE EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN.

#### Skin

WASH SKIN THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. IF SYMPTOMS PERSIST CONSULT PHYSICIAN.

#### Ingestion

DILUTE WITH WATER. DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.

#### Inhalation

REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, INSTITUTE ARTIFICIAL RESPIRATION. CONSULT WITH PHYSICIAN.

### 5. Fire Fighting Measures

**Flash Point:** 355 °F

**Autoignition Point:** N/AV °F

#### Fire And Explosion Hazards

NONE KNOWN

#### Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

#### Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

### 6. Accidental Release Measures

WEARING PROPER PROTECTIVE CLOTHING, CONTAIN SPILL AND COLLECT WITH ABSORBENT MATERIAL. SHOVEL INTO CLOSABLE CONTAINERS. AVOID CONTACT.

### 7. Handling And Storage

#### Handling And Storage Precautions

STORE IN A COOL AREA. KEEP CONTAINERS TIGHTLY CLOSED.

#### Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use with adequate general and local exhaust ventilation. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

#### Eye/Face Protection

Safety glasses with side shields or goggles.

#### Skin Protection

AVOID SKIN CONTACT. WEAR LONG SLEEVE SHIRT AND LONG PANTS.  
WEAR CHEMICAL RESISTANT GLOVES.

# MATERIAL SAFETY DATA SHEET

## Sikagard 62 - Part A (ALL COLORS)

### 8. Exposure Controls/Personal Protection - Continued

#### Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use.

#### Other/General Protection

WASH THOROUGHLY AFTER HANDLING.

#### Ingredient(s) - Exposure Limits

AROMATIC HYDROCARBON BLEND

ACGIH TLV: NOT ESTABLISHED

OSHA PEL: NOT ESTABLISHED

NTP: NO

IARC: NO

EPOXY RESIN

ACGIH TLV: NOT ESTABLISHED

OSHA PEL: NOT ESTABLISHED

NTP: NO

IARC: NO

### 9. Physical And Chemical Properties

#### Appearance

LIGHT YELLOW LIQUID

#### Odor

MILD AROMATIC ODOR

**Chemical Type:** Mixture

**Physical State:** Liquid

**Melting Point:** N/AV °F

**Boiling Point:** N/AV °F

**Specific Gravity:** 1.14

**Percent Volatiles:** 0%

**Vapor Pressure:** N/AV

**Vapor Density:** > AIR

**Solubility:** N/AV

**Evaporation Rate:** SLOWER THAN ETHER

### 10. Stability And Reactivity

**Stability:** STABLE

**Hazardous Polymerization:** WILL NOT OCCUR

#### Conditions To Avoid (Stability)

NONE KNOWN

#### Incompatible Materials

STRONG OXIDIZING MATERIALS, ACIDS AND BASES.

#### Hazardous Decomposition Products

CO, CO<sub>2</sub>, ALDEHYDES AND OTHER ORGANICS

#### Conditions To Avoid (Polymerization)

FIRES/EXOTHERM WHEN CURING IN MASS.

# MATERIAL SAFETY DATA SHEET

## Sikagard 62 - Part A (ALL COLORS)

### 11. Toxicological Information

#### Conditions Aggravated By Exposure

EYE DISEASE, SKIN DISORDERS AND ALLERGIES, CHRONIC RESPIRATORY DISEASE

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

### 14. Transport Information

#### Proper Shipping Name

NOT REGULATED UNDER D.O.T.

### 15. Regulatory Information

#### U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### SARA Hazard Classes

Acute Health Hazard  
Chronic Health Hazard

#### SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

### 16. Other Information

#### HMIS Rating

Health: 2

Fire: 1

Reactivity: 0

PPE: C

#### Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supercedes A Previous MSDS Dated: 11/27/2001

### Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A

# **M A T E R I A L   S A F E T Y   D A T A   S H E E T**

## **Sikagard 62 - Part A (ALL COLORS)**

### **Disclaimer - Continued**

MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikacorp.com](http://www.sikacorp.com) or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000